

DUMADRY Co Octoate

Cobalt Octoate

Product Description

Suitable to be used as drier with oily paints, as accelerator with polyester resins and as adhesive with rubber to metal. Used together with lead. Also used with Zirconium and Calcium to improve surface drying, in order to provide environment friendly systems. Recommended usage amount is between 0,02% - 0,05% based on solid content.

Properties	Co Oct 1	Co Oct 6	Co Oct 8	Co Oct 10	Co Oct 12
Metal Content (%)	1 ± 0.2	6 ± 0.2	8 ± 0.2	10 ± 0.2	12 ± 0.2
Appearance	Liquid	Liquid	Liquid	Liquid	Liquid
Color	Dark Blue	Dark Blue	Dark Blue	Dark Blue	Dark Blue
Viscosity (sec, 20°C)	0,50 - 0,60	1,5 - 2,5	5 - 7,5	15 - 25	100 - 150
Solid Content (%)	6 ± 2	25 ± 2	40 ± 2	50 ± 2	60 ± 2
Solvent Type	White Spirit	White Spirit	White Spirit	White Spirit	White Spirit
Density (gr/cm ³ , 20°C)	0,77 ± 0,01	0,88 ± 0,01	0,92 ± 0,01	0,97 ± 0,01	1,02 ± 0,01
Packaging (Steel Drum)	160 Kg	180 Kg	180 Kg	200 Kg	200 Kg

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.