

DUMADRY Mix

Mix Dry

Product Description

It is recommend to use DUMADRY Mix in alkyd and linseed oil coatings to speed-up drying. It is advised to use after grinding and milling stage of coatings. When formulating alkyds, it is generally used in the quantities of 0,3% - 2% of total formulation. DUMADRY Mix should be added to alkyd or other binders carefully due to its blue color, especially for clear-coats and light colors.

Properties	Mix Dry
Metal Content (%)	-
Appearance	Liquid
Color	Violet Blue
Viscosity (sec, 20°C)	2,5 - 3,5
Solid Content (%)	25 ± 2
Solvent Type	White Spirit
Density (gr/cm3, 20°C)	0,86 ± 0,01
Packaging (Steel Drum)	180 Kg

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.