

DUMADRY Mn Octoate

Mangan Octoate

Product Description

Suitable to be used instead of Cobalt driers with less drying feature. Recommended to use instead of Cobalt Octoate in dark and black colored paints. In general, recommended to use together with Lead and Calcium siccatives. It is recommended usage amount is between 0,01% – 0,06% based on solid content.

Properties	Mn Oct 6	Mn Oct 8	Mn Oct 10
Metal Content (%)	6 ± 0.2	8 ± 0.2	10 ± 0.2
Appearance	Liquid	Liquid	Liquid
Color	Dark Wine	Dark Wine	Dark Wine
Viscosity (sec, 20°C)	5,5 - 6,5	20 - 25	190 - 260
Solid Content (%)	35 ± 2	46 ± 2	65 ± 2
Solvent Type	White Spirit	White Spirit	White Spirit
Density (gr/cm ³ , 20°C)	0,92 ± 0,01	0,93 ± 0,01	0,98 ± 0,01
Packaging (Steel Drum)	180 Kg	180 Kg	200 Kg

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.