

DUMADRY Pb Octoate

Lead Octoate

Product Description

Polymerization catalyst for drying oils and provides internal drying. Lead Octoate is the most effective polymerization catalyst. Suitable to be used together with Cobalt, Calcium etc. driers. Suitable to use with oily paints as a drier and also suitable for using with grease. Not recommended to use for Aluminum coatings. It is recommended usage amount is between 0,08% – 0,6% based on solid content.

Properties	Pb Oct 24	Pb Oct 32	Pb Oct 36
Metal Content (%)	24 ± 0.2	32 ± 0.2	36 ± 0.2
Appearance	Liquid	Liquid	Liquid
Color	Light Yellow	Light Yellow	Light Yellow
Viscosity (sec, 20°C)	5 - 15	250 - 350	350 - 450
Solid Content (%)	45 ± 2	65 ± 2	70 ± 2
Solvent Type	White Spirit	White Spirit	White Spirit
Density (gr/cm ³ , 20°C)	1,09 ± 0,01	1,27 ± 0,01	1,3 5± 0,01
Packaging (Steel Drum)	220 Kg	220 Kg	275 Kg

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.