

DUMARHEO A 264

Acrylic Thickener (ASE)

Product Description

Water Based Anionic Alkali-Swellable (ASE) Thickening Agent

Technical Specifications

Appearance	:	Milky white
Total Solids (%)	:	27 - 29
Viscosity (cP, 25°C)	:	Max. 500
pH	:	3
Colloidal Charge	:	Anionic

Primary Usages

Interior Paints
Exterior Paints
Latex Coatings

Product Features

APEO free,
High viscosity levels with stability,
Excellent flowing & leveling than cellulose,
Excellent sag resistance,
Excellent resistance to microbial and enzyme attack,
Excellent roller spattering resistance

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Packaging

Net 180 Kg in Plastic Drum
Net 1050 Kg in IBC
Bulk

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.