

DUMARHEO HA 253

Acrylic Thickener (HASE)

Product Description

Water Based Anionic Mid Shear Rate Hydrophobically-Modified Alkali-Swellable Thickening Agent

Technical Specifications

Appearance	:	Milky white
Total Solids (%)	:	29 - 31
Viscosity (cP, 25°C)	:	Max. 500
pH	:	3
Colloidal Charge	:	Anionic

Primary Usages

Interior Paints
Exterior Paints
Broad range of applications

Product Features

APEO free,
Excellent mid shear stable viscosity,
Excellent flowing & leveling than cellulose,
Excellent sag resistance,
Excellent resistance to microbial and enzyme attack,
Excellent roller spattering resistance

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Packaging

Net 180 Kg in Plastic Drum
Net 1050 Kg in IBC
Bulk

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.