

DUMASOL 50 S

Elastomeric Universal Styrene Acrylic Copolymer Emulsion

Product Description

Elastomeric universal styrene acrylic copolymer emulsion that forms clear, soft, very flexible and glossy films.

Technical Specifications

Chemical Structure	:	Styrene Acrylic Copolymer
Appearance	:	White, viscous, liquid
Film Appearance	:	Clear, bright, flexible
Density (25°C, g/cm ³)	:	1,01 - 1,04
Total Solids (%)	:	49 - 51
Viscosity (cP, 25°C)	:	6.000 - 10.000
pH	:	7 - 9
MFFT (°C)	:	< 0

Primary Usages

Elastomeric Wall Paints
Exterior Paints
Textured Coatings
Plaster/Putty Coatings
Moisture Barrier Coatings
Waterproof

Product Features

Excellent elasticity
Excellent water resistance
Excellent adhesion
Broad range of applications

Storage Conditions

Protect from direct sunlight and frost. In its original packaging (plastic containers, barrels, drums, etc.), between 5 - 30°C, can be stored for 1 year.

Packaging

Net 180 Kg in Plastic Drum
Net 1050 Kg in IBC
Bulk

Material Safety

A Material Safety Data Sheet for this product is available on request.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet.